

# HERTZ



## KONSTANTIN GRCIC



**F3071064**  
 .SILVER .TRANSPARENT  
 F3071030 .BLACK .FUMEE

3 circuit track mounted, integral electronic control gear



**F3075064**  
 .SILVER .TRANSPARENT  
 F3075030 .BLACK .FUMEE

Surface mounted, integral electronic control gear



**F3065064**  
 .SILVER .TRANSPARENT  
 F3065030 .BLACK .FUMEE

Recessed plug-in stem, remote electronic control gear

**Track or ceiling/wall mounted projector, with 2 or 4 lamp configuration, integral or remote control gear**

**Hertz, Twin Optic**  
 TRACK MOUNTED, ADJUSTABLE PROJECTOR

310mm or 800mm stem

**Hertz, Twin Optic**  
 SURFACE MOUNTED, ADJUSTABLE PROJECTOR




310mm or 800mm stem

**Hertz, Twin Optic**  
 RECESSED, ADJUSTABLE PLUG-IN PROJECTOR

310mm or 800mm plug-in stem


**BODY** Aluminium/transparent or Fumee (smoked) VO polycarbonate.White or black housing  
**REFLECTOR** As per lamp selected  
**ADJUSTMENT** Horizontal 320° Vertical +/- 90° and 45° tilt

2x 35W CDMR-111 GX 8.5




AS LAMP SELECTED

2x 35W CDMR-111 GX 8.5



AS LAMP SELECTED

2x 35W CDMR-111 GX 8.5



AS LAMP SELECTED

# HERTZ



**F3095064**  
.SILVER .TRANSPARENT  
F3095030 .BLACK .FUMEE

3 circuit track mounted, integral electronic transformer


**Hertz, Quad Optic**  
TRACK MOUNTED, ADJUSTABLE  
PROJECTOR

310mm or 800mm stem

**4x 50W QR-111 G53**



35 W



AS LAMP  
SELECTED

## Lamp and Reflector Options

Low Voltage:  
G53 QR-111 (MAX 2X50W/2X75W) 8°, 24°, 45°  
G53 QR-111 (MAX 4X50W) 8°, 24°, 45°

DISCHARGE  
GX8.5 CDMR-111 (max 2x35w) 10°, 40°

## Accessories

Available with 310mm or 800mm stem  
Plug-in recessed ceiling rose for LV models,  
(Ø96, Ø70, Ø30mm)



FLOS ARCHITECTURAL